



NIPPON GOHSEI

Material Safety Data Sheet

MSDS No. 3030BK/WH-0

Effective Date: 05/30/13

[Nichigo G-Tape 3030BK/WH]

Date Printed: 10/22/16

page 1-3

1. PRODUCT : Single Sided Pressure Sensitive Adhesive Tape

Product Name : Nichigo G-Tape 3030BK & WH
Company Name: The Nippon Synthetic Chemical Industry Co., Ltd.
(NIPPON GOHSEI)
New Business Development Division
Address : Fukoku Seimei Building, 2-4, Komatsubara-cho
Kita-ku, Osaka 530-0018, Japan
Telephone: 81-6-7711-5400
Facsimile: 81-6-7711-5450
Emergency Telephone Number: 81-6-7711-5429 Adhesive Project Group

2. COMPOSITION / INFORMATION ON INGREDIENTS

| Component | CAS No. | Wt. % |
|--------------------|--------------|-------|
| Polyethylene | 9002-88-4 | 65-75 |
| Acrylic Co-Polymer | Trade Secret | 25-35 |
| Additives | Trade Secret | <1 |

3. HAZARDS IDENTIFICATION

Prolonged skin contact may cause irritation.

4. FIRST AID MEASURES

EYES : Rinse immediately with plenty of water

SKIN : Rinse with plenty of fresh water or soap with plenty of water. If inflammation appears on the skin, consult a doctor.

INHALATION of Combustion Gases : Move to the place in fresh air and call a doctor for medical care if unusual physical conditions appear.

INGESTION ; If a large amount of this tape is ingested, spew out immediately. If unusual physical condition appears, call a doctor for medical care.

5. FIRE FIGHTING MEASURES

FLASH POINT: N/A

HAZARDOUS DECOMPOSITION PRODUCTS: Hydrocarbon fragments, CO, CO₂

EXTINGUISHING MEDIA: Water, water fog, dry chemical powder, foam, and carbon dioxide

FIRE FIGHTING INSTRUCTIONS: Firemen should wear normal protective equipment (full banker gear) and positive pressure self-contained breathing apparatus.

ACCIDENTAL RELEASE MEASURES



NIPPON GOHSEI

Material Safety Data Sheet

MSDS No. 3030BK/WH-0

Effective Date: 05/30/13

[Nichigo G-Tape 3030BK/WH]

Date Printed: 10/22/16

page 2-3

Not applicable

7. HANDLING AND STORAGE

HANDLING: Avoid prolonged skin contact. Do not use as an electric insulation tape. The tape may damages surfaces and leave residue. Test before use.

STORAGE: Store in a dark and cool (below 42 degree C) place

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Not applicable

9. PHYSICAL AND CHEMICAL PROPERTIES

MELTING POINT : Polyethylene 100-125 degree C, Acrylic Copolymer N/A

SPECIFIC GRAVITY: Polyethylene 0.9 ~ 0.95, Acrylic Copolymer 1.0-1.2

Water SOLUBILITY: Insoluble

10. PHYSICAL HAZARD (STABILITY AND REACTIVITY)

CHEMICAL STABILITY: Stable

INCOMPATIBILITY: Strong oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: Hydrocarbon fragments, CO, CO₂

11. TOXICOLOGICAL INFORMATION

Not applicable

12. ECOLOGICAL INFORMATION

Not applicable

13. DISPOSAL CONSIDERATIONS

Follow all relevant instructions and regulations ruled by local, state, federal laws related to waste.

14. TRANSPORT INFORMATION

This product is not a dangerous good under the IATA regulations

15. REGULATORY INFORMATION



NIPPON GOHSEI

Material Safety Data Sheet

MSDS No. 3030BK/WH-0

Effective Date: 05/30/13

[Nichigo G-Tape 3030BK/WH]

Date Printed: 10/22/16

page 3-3

Follow all relevant regulations in your country.

16. OTHER INFORMATION

Status : Prepared by T. Yoshioka, November 11, 2011

Updated by Y. Sakaguchi, May 06, 2012

Address was updated April 1, 2014

This information is given in good faith, but no warranty, express or implied, is made.

For further information, please contact New Business Development Division, The Nippon Synthetic Chemical Industry Co., Ltd.